

5630 Memorial Ave. Ste 2 (Office) 11222 60th Street North (Plant) P.O. Box 53 (Mailing) Stillwater, Minnesota 55082 U.S.A.

Telephone: 1-651-430-2270 FAX: 1-651-430-3634

www.polywater.com custserv@polywater.com

Polywater[®] J Lubricant Environmental Statement

• Use for Green Certified Projects

Polywater[®] J meets typical LEED[®] and Green Seal criteria. This lubricant is appropriate for use during cable installation on Green Certified projects.

Low VOC Content; Meets CARB

Polywater[®] J complies with CARB regulations. It is water-based and does not contain solvents. The VOC content is 10 grams/Liter.

Non-Toxic, Safe to Use

Polywater[®] J Lubricant is non-toxic and has an estimated LD₅₀ greater than 50 gms/Kg. It does not contain carcinogens or reproductive toxins. It is not a skin sensitizer and will not cause skin or eye irritation. It does not contain ozone depleting compounds, heavy metals, phthalates, phosphates or alkyl phenol ethoxylates. Polywater[®] J Lubricant is non-combustible and safe to use.

Low Environmental Impact Packaging

Polywater[®] J Lubricant is packaged in recyclable polyethylene containers. One-gallon pail packaging meets California Title 14 with 20% source reduction.