SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

Product Name: PowerPatch[®] Putty Stick (EP-STICK) Part Numbers: 50822, 51043

Product ID numbers: EP-STICK4;

Contained in EP-KIT11, EP-KIT51, EP-KITB6, EP-KITB12, EPCT-KIT1, EPCT-KITB6; EP-XXX and EPCT-XXX (Where XXX is the package code.)

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: 2-Part Putty Sealant for temporary repair

List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

American Polywater Corporation 11222 - 60th Street North

Stillwater, MN 55082 USA Tel: 1-651-430-2270 Email: sds@polywater.com

1.4 Emergency telephone numbers

INFOTRAC 1-352-323-3500 (USA)

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to OSHA 29 CFR 1910.1200 and Regulation (EC) No 1272/2008. Skin Irritation, Cat 2; H315 Eye Irritation, Cat 2B; H319 Skin Sensitization, Cat 1; H317

reaction.

2.2 Label elements

Contains

Bisphenol A-epichlorohydrin polymer



Pictograms:	\mathbf{V}
Signal word:	Warning
Hazard Statements:	
H315	Causes skin irritation.
H317	May cause an allergic skin rea
H319	Causes serious eye irritation.
Precautionary Statem	ents:

P264	Wash thoroughly after handling.
P280	Wear protective gloves, protective clothing and eye protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.

Product Name: PowerPatch® Putty Stick

If skin irritation occurs: Get medical attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if
present and easy to do. Continue rinsing.
If eye irritation persists. Get medical attention.
No information available.

3. Composition/Information on Ingredients

<u>Component</u>	CAS #	<u>EC #</u>	<u>Wt. %</u>	GHS/CLP Classification
Bisphenol A-epichlorohydrin	25068-38-6	500-033-5	10 - 30	Skin Irrit 2, H315
polymer				Skin Sens 1, H317
				Eve Irrit 2A H319

4. First Aid Measures

4.1 Description of first aid measures

Eye Contact:	Immediately flush eyes with large quantity of water for 15 minutes. Seek medical attention.
Skin Contact:	Remove contaminated clothing; flush skin thoroughly with soap and water for at least 15 minutes. If irritation or allergic reaction occurs, seek medical attention.
Inhalation (Breathing):	If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention.
Ingestion (Swallowing):	No emergency medical treatment necessary

4.2 Most important symptoms and effects, both acute and delayed Refer to Section 11 for more information.

4.3 Indication of immediate medical attention and special treatment needed. No information available.

5. Firefighting Measures

5.1 Extinguishing media:

Water fog or fine spray, dry chemical carbon dioxide, or foam.

5.2 Special hazards arising from the substance or mixture

Dense smoke is emitted when burned without sufficient oxygen.

Hazardous decomposition and by-products:

CO₂, CO, phenolics. May contain other combustion products of varying composition which may be toxic or irritating.

5.3 Advice for firefighters

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Water fog may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture. Direct water stream may spread fire.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate area. Use appropriate safety equipment.

6.2 Environmental precautions:

Avoid release to the environment. Prevent spill from entering drainage/sewer systems, waterways, basements or confined areas. Refer to Section 12 for more information.

6.3 Methods materials for containment and cleaning up:

Absorb spill with sand or absorbents. Residual resin may be removed using steam or hot soapy water. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Residual material can be removed with solvent.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage

7.1 Precautions for safe handling

Avoid personal contact with the product. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

7.2 Conditions for safe storage, including incompatibilities

Keep containers cool, dry, and away from sources of ignition. Keep containers and cartridges capped and sealed. Protect from freezing. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

7.3 Specific end uses

See technical data sheet on this product for further information.

8. Exposure Controls / Personal Protection

8.1 Control parameters

Exposure limits and recommendations:

Contains no components with established Occupational Exposure Limit (OEL) values. A Derived No Effect Level (DNEL) of 12.25 mg/m³ has been established for Acute Inhalation.

8.2 Exposure controls

Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced. Use a respirator or gas mask with cartridges for organic vapors (NIOSH or CE approved) with particulate pre-filter, P100 or AP2.

Protective gloves:

The use of chemically resistant gloves is recommended to prevent skin contact. Suitable materials include nitrile (included in most kits), neoprene, ethyl vinyl alcohol (EVAL), PVC. Use a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374). NOTE: The selection of specific glove for the application should account for other chemicals in the environment, physical requirements and potential user reaction to the glove material.

Eye protection:

Safety glasses recommended.

Other protective equipment:

Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

9. Physical and Chemical

9.1 Information of basic physical and chemical properties

Appearance:	Gray/dark gray, solid putty stick. Pungent, sulfurous odor.
Odor threshold:	Not available
pH:	Not available
Freezing point:	Not available
Boiling point:	Not available
Flash point:	>199.9°F / >93.3°C (PMCC)
Evaporation rate:	Not available
Flammability (solid, gas):	Not available
Upper/lower flammability or explosive limits:	Not available

Vapor pressure:	Not available
Vapor density (Air = 1):	Not available
Specific gravity (H ₂ O = 1):	2.247
Solubility in water:	Not available
Partition coefficient: n- octanol/water:	Not available
Auto-ignition temperature:	Not available
Decomposition temperature:	>392°F / >200°C
Viscosity:	Not available (thick putty)
0.2 Other Information	
Volatiles (Weight %):	<0.1%
VOC Content:	0 g/l

10. Stability and Reactivity

10.1 Reactivity:

9

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

Hazardous reactions will not occur under normal transport or storage conditions.

10.4 Conditions to avoid:

Avoid high temperatures above 300 °C (572 °F). Decomposition can occur above 350 °C (662 °F). Generation of gas during decomposition can cause pressure to build in closed systems.

10.5 Incompatible materials :

Strong acids or bases (especially primary or secondary aliphatic amines), strong oxidizing agents.

10.6 Hazardous decomposition products:

CO₂, CO, phenolics and other organic substances may be formed during combustion or elevated temperature degradation.

11. Toxicological Information

11.1 Information on toxicological effects: Acute toxicity

Eye contact:

Direct eye contact with material or vapors may cause eye irritation.

Skin contact:

This product has moderate skin irritation potential. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material. Prolonged or repeated skin exposure may cause skin sensitization.

Irritation and Sensitization Potential:

May cause allergic skin reaction.

Inhalation (Breathing):

Low vapor pressure makes this route of exposure unlikely.

Ingestion:

Ingestion may cause irritation of the gastrointestinal tract.

Toxicity to Animals:

Bisphenol A Diglycidyl Ether:

LD₅₀ (oral rat) >15,000 mg/kg LD₅₀ (dermal rabbit) 23,000 mg/kg

Aspiration Hazard:	
No aspiration hazard expected	I.
Chronic Exposure:	
Reproductive Toxicity: Mutagenicity:	Not available. Resins based on diglycidyl ether of bisphenol A have proved to be inactive when tested by in-vivo mutagenicity assays. These resins have shown activity in in-vitro microbial mutagenicity screening and have produced chromosomal aberrations in cultured rat-liver cells. The significance of these tests to humans is unknown.
Teratogenicity:	Not available.
Specific Target Organ	
Toxicity (STOT)	Not available.
Toxicologically Synergistic	
Products:	Not available.
Carcinogenic Status:	This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components.

12. Ecological Information

12.1 Toxicity:	
Aquatic Toxicity:	May be toxic to aquatic organisms.
Bisphenol A Diglycidyl	LC ₅₀ (96 hr): 2 mg/l Oncorhynchus mykiss (rainbow trout)
Ether:	Semi-static test
Bisphenol A Diglycidyl	EC ₅₀ (48 hr): 1.8 mg/l Daphnia magna (invertebrate)
Ether:	Static test
Bisphenol A Diglycidyl	ErC ₅₀ (72 hr): 11 mg/l Fresh water algae (aquatic plants)
Ether:	Static test
	Chronic Toxicity Value:
Bisphenol A Diglycidyl Ether:	Daphnia magna (invertebrate),21 d, number of offspring, NOEC: 0.3 mg/l Semi-static test
12.2 Persistence and	Based on stringent OECD test guidelines, this material cannot be
degradability:	considered readily biodegradable. Biodegradability depends on environmental conditions.
Bisphenol A Diglycidyl	OECD Biodegradation Test 302B
Ether:	12% Biodegradation, 28 d exposure
Bisphenol A Diglycidyl	Theoretical Oxygen Demand
Ether:	2.35 mg/mg
12.3 Bioaccumulation	
potential:	Bioconcentration potential is moderate.
12.4 Mobility in soil:	Potential for mobility in soil is low
12.5 Results of PBT and	
vPvB Assessment:	This product is not, nor does it contain a substance that is a PBT or vPvB.
12.6 Other adverse effects:	None known.

13. Disposal Considerations

Do not dump into sewer, on ground or into any body of water. Dispose of product in accordance with National and Local Regulations.

14. Transport Information

DOT:	Not Regulated
UN Number:	3077
UN Proper Shipping Name:	Environmentally hazardous substance, solid, N.O.S. (Bisphenol A)
Class and Subsidiary Risk:	9
Packing Group:	III

Not Regulated (See Special Provision A197)
Not Regulated (See IMDG Code 2.10.2.7)
9
For surface shipments within the United States: Not regulated.

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

USA Federal and State

All components are listed on the TSCA inventory.

Hazard Categories for SARA	Acute	<u>Chronic</u>	<u>Fire</u>	<u>Pressure</u>	Reactive	
Section 311/312 Reporting	Yes	Yes	No	No	No	

	CERCLA/SARA Sec 302		SARA Sec. 313
<u>Components</u>	Hazardous Substance RQ	<u>EHS TPQ</u>	Toxic Release
Components are not affected by these Superfund regulations.			

NFPA Ratings:	Health:	2
-	Fire:	1
	Reactivity:	0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

European Union

All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. It does not contain Substances of Very High Concern (SVHC).

Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Classification:

Class D, Division 2B

Australia

All components are listed on the AICS. Product is classified as hazardous according to criteria of NOHSC Australia.

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

16. Other Information

Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration CLP = Classification, Labeling and Packaging Regulation STOT = Specific Target Organ Toxicity LD₅₀ = Median Lethal Dose DNEL = Derived No Effect Level ACGIH = American Conference of Governmental Industrial Hygienists TSCA = Toxic Substances Control Act (USA) DSL = Domestic Substances List (Canada) AICS = Australian Inventory of Chemical Substances

Product Name: PowerPatch[®] Putty Stick

Hazard Statements:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Revision Date: Revision Number:	July 22, 2015 6
Supersedes:	November 25. 2014
•	
Other:	Not Applicable
Indication of Changes:	Section 1.1 product identifier updated in accordance with the provisions of OSHA
	1910.1200 App D and REACH Annex II (EU No 453/2010). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.