SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

Product Name: HotStick Cleaner/Water Repellent Wipe Type S

Product ID numbers: S-1, S-1C, S-1M, S-1-50

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses:	Surface treatment, cleaner & water repellent
------------------	--

List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

American Polywater Corporation 11222 - 60th Street North Stillwater, MN 55082 USA Tel: 1-651-430-2270 Email: sds@polywater.com Polywater Europe BV Zuidhaven 9-11 Unit B2 4761 CR Zevenbergen Netherlands Tel: +31 (0)10 2330578 Email: sds@ polywater.com

1.4 Emergency telephone numbers

INFOTRAC 1-352-323-3500 (USA)

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to OSHA 29 CFR 1910.1200 and Regulation (EC) No 1272/2008.

Flam Liq 2	H225
Eye Irrit. 2	H319
STOT SE 3	H336

2.2 Label elements

Contains:



Pictograms: Signal word:

Hazard Statements:

H225 Highly flammable liquid and vapor

Danger

- H319 Causes serious eye irritation
- H336 May cause drowsiness or dizziness

Precautionary Statements:

P210	Keep away from sparks, flames and hot surfaces. No smoking.
P261	Avoid breathing vapor.
P280 P304 + P340	Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + +P351 +	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

Product Name: HotStick [*]	[®] Cleaner/Water Repellent Wipe Type S	Revision Date: January 2, 2015
P338	if present and easy to do. Continue rinsing.	
P370 + P378	In case of fire: Use water fog, foam, dry chemic	cal or carbon dioxide for extinction.
2.3 Other hazards:	No information available.	

3. Composition/Information on Ingredients				
<u>Component</u>	<u>CAS #</u>	<u>EC #</u>	<u>Wt. %</u>	GHS/CLP Classification
Isopropanol	67-63-0	200-661-7	80 – 90 < 10 grams/towel	Flam Liq 2 H225; Eye Irrit. 2 H319; STOT SE 3; H336

This product contains no other reportable hazardous components under 29 CFR 1910.1200. This product contains no other reportable hazardous components under European Directives 91/55/EEC.

4. First Aid Measures

4.1 Description of first aid measures

Eye Contact:	If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.
Skin Contact:	Remove contaminated clothing; flush skin thoroughly with water. If irritation occurs, seek medical attention.
Inhalation (Breathing):	If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention. If breathing is difficult, provide oxygen. If not breathing, give artificial respiration. Seek immediate medical attention.
Ingestion (Swallowing):	Do not induce vomiting or give anything by mouth unless directed to do so by medical personnel. Get medical attention if symptoms appear.

4.2 Most important symptoms and effects, both acute and delayed Refer to Section 11 for more information.

4.3 Indication of immediate medical attention and special treatment needed.

Causes serious eye irritation.

5. Firefighting Measures

5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition and by-products:

Burning generates carbon monoxide, carbon dioxide.

5.3 Advice for firefighters

Wear appropriate, protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Limited spill hazard with saturated towel package. For small spills: normal antistatic work clothes are usually adequate.

6.2 Environmental precautions:

Avoid release to the environment.

6.3 Methods materials for containment and cleaning up:

Collect towel and absorb any excess material with sand or absorbents.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage

7.1 Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use only outdoors or in a well-ventilated area. For industrial or professional use only.

7.2 Conditions for safe storage, including incompatibilities

Store in a well-ventilated place. Keep cool. Store away from acids and oxidizing agents.

7.3 Specific end uses

See technical data sheet on this product for further information.

8. Exposure Controls / Personal Protection

8.1 Control parameters

Exposure limits and recommendations:			
Component Name	Limit	Standard	Source/Note
Isopropanol	TWA 400 ppm	OSHA, NIOSH	USA
	TWA 400 ppm	EH40/2005 WEL	UK

8.2 Exposure controls

Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

Protective gloves:

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Eye protection:

Safety glasses recommended.

Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

9. Physical and Chemical

9.1 Information of basic physical and chemical properties (bulk liquid)

Appearance:	Clear, colorless liquid; typical alcohol odor.
Odor threshold:	22 ppm (isopropanol)
pH:	Does not apply
Freezing point:	-130°F / -90°C (isopropanol)
Boiling point:	180°F / 82°C (isopropanol)
Flash point:	55°F / 13°C (TCC)
Evaporation rate:	1.7 (n-butyl acetate = 1), isopropanol
Flammability (solid, gas): Upper/lower flammability or	Not applicable to liquids LEL: 2% (isopropanol)
explosive limits:	UEL: 12.7% (isopropanol)
Vapor pressure:	4.4 kPa @20°C (isopropanol)
Vapor density (Air = 1):	2.1 (Air = 1)
Specific gravity (H ₂ O = 1):	0.79

Solubility in water: Coefficient of Water/Oil	Dilutes
Distribution:	0.1 This product is equally soluble in oil and water.
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available
Viscosity:	Not available
9.2 Other Information	
Volatiles (Weight %):	85%
VOC Content:	675 g/l

10. Stability and Reactivity

10.1 Reactivity:

9

See remaining headings in Section 10.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

None known.

10.4 Conditions to avoid:

Avoid heat, flame, and sparks.

10.5 Incompatible materials :

Strong oxidizing agents.

10.6 Hazardous decomposition products:

Carbon dioxide, carbon monoxide.

11. Toxicological Information

11.1 Information on toxicological effects:

Acute toxicity

Eye contact:

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

Skin contact:

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

Irritation and Sensitization Potential:

Product may be irritating to skin and eyes. It is not a sensitizer.

Inhalation (Breathing):

Concentrated solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue.

Ingestion:

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

Toxicity to Animals:

Isopropanol	LD ₅₀ (oral rat) 5000 mg/kg
	LD ₅₀ (dermal rabbit) 12800 mg/kg
	LC ₅₀ (inhl rat) 12000, 8 hours
Chronic Exposure:	
Reproductive Toxicity:	Not classified as a reproductive system toxin.
Mutagenicity:	Not classified as a mutagen.

Teratogenicity: Specific Target Organ	Not classified as teratogenic or embryotoxic.
Toxicity (STOT)	No end point data.
Toxicologically Synergistic	
Products:	Not available.
Carcinogenic Status:	This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components.

12. Ecological Information

12.1 Toxicity:	
Ecotoxicity:	No information available.
Aquatic Toxicity (Isopropanol):	
Fish (acute)	96 h LC ₅₀ Fathead Minnow > 1000 μl/l
	48 h LC ₅₀ Golden Orfe 8970 - 9280 mg/l
Aquatic crustacea (acute)	96 h LC ₅₀ Daphnid > 1000 μl/l
12.2 Persistence and degradability:	No information available
12.3 Bioaccumulation potential:	No information available
12.4 Mobility in soil:	No information available
12.5 Results of PBT and vPvB	This product is not, nor does it contain a substance that is a
Assessment:	PBT or vPvB.
12.6 Other adverse effects:	None known.

13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

14. Transport Information

US DOT Domestic Ground	
Transportation:	Not Regulated (See Special Provision 47).
UN Number:	3175
UN Proper shipping name:	Solids Containing Flammable Liquid, N.O.S., (Contains: Isopropanol)
Transport hazard class(es):	Class 4.1
Packing group:	II
Environmental hazards:	None known
Special precautions:	None known
ICAO/IATA-DGR:	Not Regulated (See Special Provision A46)
IMDG:	Not Regulated (See Special Provision 216)

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

USA Federal and State

All components are listed on the TSCA inventory.

Hazard Categories for SARA	Acute	<u>Chronic</u>	Fire	Pressure	Reactive
Section 311/312 Reporting	Yes	No	Yes	No	No

CERCLA/SARA Sec 302

SARA Sec. 313

Hazardous Substance RQ

Toxic Release

Components are not affected by these Superfund regulations.

NFPA Ratings:	Health:	1
-	Fire:	3
	Reactivity:	0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

EHS TPQ

European Union

Components

All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. It does not contain Substances of Very High Concern (SVHC).

Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

WHMIS Classification:

Australia

All components are listed on the AICS. Hazardous according to criteria of NOHSC Australia.

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

B2

16. Other Information

Abbreviations and acronyms:

 $\begin{array}{l} \text{OSHA} = \text{Occupational Safety and Health Administration} \\ \text{CLP} = \text{Classification, Labeling and Packaging Regulation} \\ \text{STOT} = \text{Specific Target Organ Toxicity} \\ \text{LD}_{50} = \text{Median Lethal Dose} \\ \text{DNEL} = \text{Derived No Effect Level} \\ \text{ACGIH} = \text{American Conference of Governmental Industrial Hygienists} \\ \text{TSCA} = \text{Toxic Substances Control Act (USA)} \\ \text{DSL} = \text{Domestic Substances List (Canada)} \\ \text{AICS} = \text{Australian Inventory of Chemical Substances} \\ \end{array}$

Hazard Statements:

H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
Revision Date:	January 2, 2015
Revision Number:	5
Supersedes:	November 26, 2014
Other:	Not Applicable
Indication of Changes:	Section 1, 2, 15, 16 updated. Addition of acronyms and other formatting changes.
	Updated in accordance with the provisions of OSHA 1910.1200 App D and REACH
	Annex II (EU No 453/2010). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.